

Total Cooling Solutions

Integral Island freezer/chiller



NEW Product

Norwell 150 Integral Island Freezer/Chiller

A versatile display that increases impulse sales

The Norwell freezer/chiller island is extremely effective in prompting shoppers to make impulse purchases. Its small size means that it can be located practically anywhere. It is difficult for shoppers to pass a Norwell island without buying when the products in its glass display can be clearly seen from long distances and all directions.

The Norwell display island is suitable for all types and all sizes of stores and shops - from supermarkets to convenience stores and from service stations to kiosks.

Cabinet Code	Norwell-100-M-C	Norwell-150-M-C	Norwell-150-M-FF	Norwell-150-M-FC
Product range	Norwell	Norwell	Norwell	Norwell
Cabinet description	Integral refrigerator unit	Integral refrigerator unit	Integral freezer unit	Integral refrigerator / freezer unit
Height	915mm	915mm	915mm	915mm
Depth	880mm	1055mm	1055mm	1055mm
Width	1055mm	1515mm	1515mm	1515mm
Cabinet finish	White	White	White	White
Power supply	13 amp	13 amp	13 amp	13 amp
Capacity	138 Litres	277 Litres	277 Litres	277 Litres
Temperature range	+2...+4°C	+2...+4°C	-23...-21°C	Chiller Version +2...+4°C Freezer Version -23...-21°C
Refrigerant	R404A	R404A	R404A	R404A

Construction

- load-bearing structure and outer shell: All visible elements of the top part are made of aluminium profile. The grey base element and the detachable panels in the top part are made of galvanised steel sheet
- the glass panel beading encircling the unit is also made of aluminium
- high quality, durable stove enamelling
- insulation is pressure-foamed polyurethane applied by an automated machine, causing no harmful effects to the ozone layer
- castor wheel mounting for ease of movement around the shop
- the high glass edge maximises the visibility of products in the unit

Models

- refrigerator unit (C) +2...+4°C
- refrigerator/freezer unit (FC) +2...+4°C / -23...-21°C
- freezer unit (FF) -23...-21°C
- FC model with electric defrosting
- FF model with hot gas defrosting

Standard equipment

- integrated cooling machinery with fan evaporator
- automatic defrosting and drainwater evaporation
- connection lead with earthed plug
- castor wheels (4)
- lighting all around the unit on the top edge of the glass panel

Optional accessories

- plastic cover
- advertising light (2 separate lights)
- brake (2 pcs per unit)
- partition dividers
- electric socket on base
- exchangeable side panels

Technical specifications at ambient temperature of +25°C and relative humidity of 60%.

Connection voltage 230V, single-phase, 50Hz.